

## Jupiter Downlight

### Specifications

#### Output

<b>Luminous Flux</b>	Up to 380Lm (12W)
<b>Efficacy</b>	31(±5)Lm/W
<b>CCT</b>	3000K, 4000K
<b>CRI</b>	Ra90
<b>Beam Angle</b>	20°
<b>Life Time</b>	>50,000Hrs (Ta=30°C@L70)

#### Electrical

<b>Input Voltage</b>	240 VAC
<b>Power Factor</b>	≥0.9
<b>Frequency</b>	50 Hz

#### Construction

<b>Product Dimension</b>	110mm x 94mm
<b>Cutout</b>	104mm
<b>Fixture Color</b>	White, Silver, Black
<b>IP Rating</b>	IP20
<b>Mounting</b>	Recessed
<b>Rotation</b>	Adjustable

#### Control


<b>Dimmable</b>	Various Dimming Profiles Available
-----------------	------------------------------------

#### Thermal

<b>Operating Temperature</b>	-20°C to + 40°C
------------------------------	-----------------

#### Warranty

<b>Years</b>	5
--------------	---



### Catalogue Number Guide: Forlite VUE Jupiter Downlight

<b>FV</b>	<b>J</b>	<b>5</b>	<b>D1</b>	<b>20</b>	<b>4</b>	<b>W</b>	<b>G</b>	<b>R</b>
<b>Product Group</b>	<b>Group Destination</b>	<b>Wattage</b>	<b>Dimmable</b>	<b>Beam Angle</b>	<b>Colour Temperature</b>	<b>Fixture Colour (Outer)</b>	<b>Fixture Colour (Inner)</b>	<b>Mounting</b>
<b>FV</b> Vue	<b>J</b> Jupiter	<b>5</b> 5W <b>8</b> 8W <b>10</b> 10W <b>12</b> 12W	<b>D1</b> 1-10V <b>DD</b> DALI <b>DO</b> Non Dim <b>CS</b> Casambi	<b>20</b> 20°	<b>4</b> 4000K <b>3</b> 3000K	<b>W</b> White <b>S</b> Silver <b>B</b> Black	<b>G</b> Gold <b>S</b> Silver <b>B</b> Black	<b>R</b> Recessed

**CASAMBI**