

Slim Wall Light

Specifications

Output

Luminous Flux	2250Lm (30W)
Efficacy	75(±5)Lm/W
CCT	3000K or 4000K
CRI	Ra90
Beam Angle	20°, 26°, 35°
Life Time	>50,000Hrs (Ta=30°C@L70)

Electrical

Input Voltage	240 VAC
Power Factor	≥0.9
Frequency	50 Hz

Construction

Product Dimension	55mm x 250mm
Housing	Aluminium
Optics	PMMA Optical Lens
Finish	Powder Coated
Fixture Colour	White, Black, Silver
IP Rating	IP20
Mounting	Wall Mount

Control


Dimmable	Various Dimming Profiles Available
-----------------	------------------------------------

Thermal

Operating Temperature	-20°C to + 40°C
------------------------------	-----------------

Warranty

Years	5
--------------	---



Catalogue Number Guide: Forlite TESO Slim Wall Light

FT	-	S	-	30	-	D1	-	20	-	4	-	W	-	W	-	T
Product Group		Group Destination		Wattage		Dimmable		Beam Angle		Colour Temperature		Fixture Colour (Outer)		Fixture Colour (Inner)		Mounting
FT Teso		S Slim		30 30W		D1 1-10V DD DALI D0 Non-Dim CS Casambi		20 20° 26 26° 35 35°		4 4000K 3 3000K		W White S Silver B Black		W White S Silver B Black G Gold		WM Wall Mount

CASAMBI